



DECLARATION OF PERFORMANCE

DoP No. : W29SE HYB100

1. Unique identification code of the product-type: W29SE HYB001

2. Type or any other element allowing identification of the construction product as required pursuant to Article 11(4) :
NMC DOMOSTYL® Hybrid

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Sealant for facade for interior and exterior application

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
NMC sa, Gert-Noël-Straße, B-4731 Eynatten

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: 3
3: for reaction to fire

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard :
GINGER CEBTP - NB 0074

9. Declared performance according to EN 15651-1:2012

Characteristics	Performances
Reaction to fire (Euroclass)	E
Release dangerous chemicals	NPD
Water and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10 %
Elastic recoverv	≥ 60 %
Secant modulus at 23 ° C(N/mm ²)	> 0,4
Secant modulus at - 20 ° C(N/mm ²)	> 0,6
Tensile properties at maintained extension	NF
Adhesion/cohesion at variable temperatures	NF
Adhesion/cohesion at maintained extension after water immersion	NF
Durability(conformity)	OK

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
Signed for and on behalf of the manufacturer by:

Name and function : X. FISCHER
Quality Manager

Eynatten, 27/05/14